## QUALITY SPECIFICATIONS





Structure: Reinforced concrete.

Foundation: reinforced concrete footings Terraces: reversed flat roof, thermal insulation, with 80mm extruded polystyrene XPS rigid planks.

Outdoors paving: Non-slip and freezingresistant pavements on walkable areas. Coating: 2 layers of water-resistant

Facades: 24x12x10cm brick, with a onelayer plastering+ closed-cell structure extruded polystyrene panels (XPS)+ Perforated ceramic brick.

Party walls: Double layer of double-hollowed ceramic brick with a chamber and Rockwool insulation in party walls in the houses. Air soundproofing

House Inner flooring: 60x60cm porcelain

House wet areas flooring: 60x60cm porcelain tiles.

Terrace and covered areas pavement: porcelain tiles, with slip-resistant treatment. Kitchen flooring: 60x60cm porcelain tiles. Stairs flooring: outdoors specific with slipresistant treatment

Paint: smooth paint in general and enamelled in the bathrooms.

Bathroom cladding: ceramic tiling False ceiling: Plasterboard

panelled/suspended false ceiling depending on the area.

Special features, In specific areas, hidden RGB LED linear light in the ceiling plasterboard (\*).



Doors: 35mm white-enamelled MDF board doors from the floor to the ceiling

Entrance door: armoured white-coloured in the exterior side

Wardrobes: with lacquered white matt and upper shelves. Textured interior finishing. Drawers, bars and shelves.

Board skirting: High white-enamelled MDF

Metalwork: Tilted, fixed and sliding with anodized grey-lacquered thermal break aluminium profile and motorized shutter. Glazing: All metalwork glazed with Climalit

and laminated safety glass.



WC with built-in tank and a flush button. Sinks on counter.

BasinTaps: Wall-mounted taps for basins Shower taps: Wall-mounted taps for showers composed of: bath and shower single-lever mixer tap + showerhead + adjustable base with water intake. Showers with a ground-level tray

Screens: Safety-glass fixed screens in bathrooms.

Mirrors.





Telecommunications installation according to the Regulations on Common Telecommunication facilities. Integrated Services Digital Network (Channelling) to install cable TV. Installation of a video intercom with a colour screen

Alarm installation with volumetric sensors and an interior siren. (\*)

Individual DHW production, by means of a highly energy-efficient heating pump. Heating and air-conditioning pre-installation by ducts along the whole house by an individual heating pump, an external unit on the roof, an interior unit on the false ceiling in the secondary bathroom and impulsion ducts in grids.



Bright white or grey household appliances.

Counter: type white Dalian or type white Silestone. Built-in sink Single-lever tap with aerator. Equipped with an extractor hood.



Pedestrian access gate (GF units) with galvanized and lacquered steel frame and aluminium slats. Mailbox and house

Motorized sliding access gate for vehicles Non-slip outdoors paving

Landscaping: sellection of mediterranean vegetation in the community areas and darden lightning system.